# CITY OF ALBANY PLANNING AND ZONING AGENDA STAFF REPORT

Agenda date: October 11, 2011

Prepared by: ALH

ITEM: 6C

SUBJECT: Planning Application 11-048. Design Review 918 Cerrito St. The applicant is seeking approval of the following:

- Design Review approval for a second story addition of three (3) bedrooms and two (2) baths. The existing home has two (2) bedrooms and two (2) baths and is located on a 2,500 sq. ft. lot.
- Approval of parking variance to allow one (1) off-street parking space to encroach into the front yard setback.

Under the proposed application request, the home will have five (5) bedrooms and four (4) baths and be located on a 2,500 sq. ft. lot.

SITE: 918 Cerrito St.

OWNER: Derek Small & Kim Bollin

APPLICANT: Howard McNenny, Architect

**ZONING:** R-1 (Single-Family Residential)

#### STAFF RECOMMENDATION

Due to the proposed size of a five (5) bedroom, four (4) bath home on a 2,500 sq. ft. lot, it is recommended that the Planning and Zoning Commission review the proposed application and provide design feedback to the applicant and staff.

#### **BACKGROUND/PROJECT DESCRIPTION**

The subject property is a 2,500 square foot lot with an existing 1,555 square foot single-story home with a finished basement. The basement contains a finished bedroom, family room, and bathroom and is 707 sq. ft. in area. The existing first floor area is 847.5 sq. ft and contains a bedroom, bathroom, kitchen with dining area, and living room.

The applicant is proposing to add a second story approximately 652.5 sq. ft in area which will contain three (3) bedrooms and two (2) baths. The addition will be stacked at the rear of the home and have a stucco finish. The height of the residence is proposed to increase to 24 feet from 18 ft.

The applicant is also seeking a parking variance to allow one (1) off-street parking space to be located in the front yard setback. The other off-street parking will be provided in the single-car garage.

# **ENVIRONMENTAL ANALYSIS**

Staff has determined that the proposed project is categorically exempt from the requirements of the California Environmental Quality Act (CEQA) per Section 15303 "New Construction or Conversion of Small Structures" of the CEQA Guidelines, which exempts small additions.

# **SITE LOCATION**



**Figure 1. Site Location** 

# **DISCUSSION OF KEY ISSUES**

# Floor Area Ratio (FAR)

The applicant is seeking an exception to the FAR pursuant to Albany Municipal Code Section 20.24.050 (B) (2) (a) where the Planning Commission may approve an FAR of up to .6 if a determination can be made to support the application request. Given the project scope, the applicant is asking the Commission to make an exception pursuant to the following:

a. The site is of such a size that application of the .55 floor/area ratio would result in a gross square footage of less than one thousand five hundred (1,500) square feet.

As the project is currently proposed, the FAR is .6. The total floor area is 1,499.5 sq. ft. on a 2,500 sq. ft. lot. To satisfy the standard .55 FAR, the maximum area is 1,375 sq. ft. on a 2,500 sq. ft. lot.

# Basement Exclusion from FAR

The applicant indicated in the project description that the entire ground level was excluded from the FAR calculations due to Section 20.24.050 Floor-Area Ratios (B) (1) (c) of the Albany Municipal Code. This Code provision reads as follows:

c. Any covered area on or below the first or main floor, shall be considered a story and shall be calculated in the floor-area ratio if the average height of the perimeter is greater than five (5) feet, except a single parking area may be excluded as provided in paragraph B.1.b. above. Measurement of height shall be taken from the lower of natural or finished grade at the exterior to the top of finished floor of the first, main or story above.

Staff asked the applicant to provide a table with the average perimeter height information to support their request to exclude the converted basement area from the FAR calculations. The applicant provided us with the information below and indicated that the average height is 4.83 ft.

Average height of perimeter of Areas A + B calculated as follows:

South wall: 35.42 ft @ average ht. of 4.92 ft West wall: 19.13 ft @ average ht. of 4.33 ft North wall: 39.00 ft @ average ht. of 5.00 ft

Average height = 4.83 ft

Figure 2. Average Perimeter Height Information from the applicant

Additionally, Section 20.24.050 (B) (1) (b), one (1) parking space maybe excluded, up to 220 sq. ft., from the FAR calculation. This exclusion is noted on the plans.

# **Exterior Elevations**

The existing residence is single-story, with a flat roof and stucco finish. The applicant is seeking approval to add a second story to the existing home. The second story is proposed to be setback 14'9" from the front of the existing home in an effort to reduce bulk. The addition will have a simple hipped roof. The first story elevation roofline will be modified to a simple hipped roof and will match second story addition roof. A second story deck off of the master suite is proposed. The hand railings will match the existing railings of the home.

Skylights are proposed for the second-story roof and will be located above the bathrooms and stairwell. Bamboo, fruit trees, and a vegetable garden are planned as part of the new landscaping scheme.

There is an unfinished deck off of the rear of the home. Previously, the property owner submitted preliminary plans for the deck but never applied for a building permit. The deck was substantially constructed and is shown on the plans as not completed.

Photos 1-4 show the existing home, railing details, existing windows, and proposed windows.



Photo 1. Existing Home




Photo 2. Railing Detail



Photo 3. Existing Window



Photo 4. Proposed Window

#### <u>Parking</u>

The applicant is seeking an exception to allow one (1) off-street parking space to encroach in the front yard setback. One covered parking space is provided within the existing garage. The front yard uncovered driveway parking area measures  $12' \times 15'$ . Per Section 20.58.050 (d), an open air single parking space is required to measure a minimum of  $7'6'' \times 16'$ .

d. Open or Covered Parking (Pre-1978). Where warranted by spatial limitations related to construction approved prior to the enactment of Measure D¹ in November 1978, the Planning and Zoning Commission may permit an open or covered parking space measuring no less than seven (7) feet six (6) inches wide, by sixteen (16) feet long, to meet off-street parking requirements. The Commission may permit a minimum width dimension for a double-car open or covered parking space to be fourteen (14) feet. All minimum width dimensions shall be increased by one (1) foot of width adjacent to each wall, fence, property line or other fixed obstruction that restricts access abutting the long dimension of the parking space.

#### Residential Design Guidelines

Consistency with the City's Residential Design Guidelines is detailed below.

- 1. The front yard is the house's contribution to the street.
  - There is existing landscaping and decorative tile flatwork in the front of the home. Additionally, there are decorative planter boxes with shrubbery located in the front yard.
- 2. Every house needs a usable front porch
  - There is an existing front porch landing area located in front of the main entrance.
- 3. Garages should have single-car doors and be attractive

- There is an existing wood garage door at the home.
- 4. Increasing the livability of the home
  - The home will increase in area from 847 sq. ft. (2 bedroom, 2 bath) to 1,499.5 sq. ft. (5 bedroom, 4 bath)
- 5. Dormers and bays are encouraged
  - Dormers and bays are not proposed as part of this project.
- 6. Trim and details give a house warmth and character
  - The home is proposed to be stucco. Decorative trim is not proposed.
- 7. Building Materials
  - The applicant is proposing a stucco addition to match the existing stucco.
- 8. Green Building
  - The applicant has provided the supplemental application form detailing the "green" efforts to be made as part of the project construction. This includes low VOC paints, energy star appliances, and seismic upgrade of the existing building. The Checklist provided by the applicant indicates a total score of 71 points.
- 9. Second-Units and Multi-family housing
  - N/A
- 10. Landscaping is an important aesthetic element of home design
  - Bamboo, fruit trees, and a vegetable garden are planned as part of the new landscaping scheme.

#### **Attachments:**

- 1. Analysis of Zoning Requirements
- 2. Draft Findings for Approval
- 3. Draft Conditions of Approval
- 4. Project Application & Plans

# ATTACHMENT 1 - ANALYSIS OF COMPLIANCE WITH ZONING REQUIREMENTS

# 20.12 Zoning Districts and Permitted Uses

General Plan: Low Density Residential

Zoning: R-1 – Single-Family Residential

# 20.16 Land Use Classifications

Single family residential

Surrounding North - SFR East - SFR
Property Use South - SFR West - SFR

# 20.20.080 Secondary Residential Units.

Not applicable.

# 20.24.020 Table of Site Regulations by District.

	Existing (approx.)	Proposed Construction (approx.)	Requirement
Setbacks	(прртох.)	(upprox.)	
Front (east)	15′	No change	15′
Side (north)	3′	No change	3'9"
Side (south)	3′	No change	3'9"
Rear (west)	33'9"	20′	20"
Area			
Lot Size	2,500	No change	
Lot Coverage	37%	No change	50%
Maximum Height	18′	24′	28′ max.

# 20.24.030 Overlay District Regulations.

Not applicable.

# 20.24.040 Hillside Residential Regulations.

Not applicable

# 20.24.050 Floor-Area-Ratio.

	Existing (approx.)	Proposed	Requirement
Lot Size	2,500	No change	
Floor Area			
Garage/Storage	707.6	707.6	
Main Level	847	847	
Second-floor	N/A	652	
Total			
Total Counted*	1,041	1499.5	
Floor Area Ratio*	29%	60%	55%

<sup>\* 707.6</sup> sq. ft. exempted from "total counted" as permitted by AMC 20.24.050 for garage and stairs & Section 20.24.050 Floor-Area Ratios (B) (1) (c).

# 20.24.060 Setback Areas, Encroachments.

Not applicable.

#### 20.24.100 Distances between Structures.

Not applicable.

# 20.24.110 Fences, Landscaping, Screening.

New landscaping is proposed as part of the project scope and includes bamboo, fruit trees, and a vegetable garden.

#### 20.24.130 Accessory Buildings.

Not applicable.

# 20.28 Off-Street Parking Requirement.

See Discussion of Key Issues.

#### 20.40 Housing Provisions

Not applicable.

# 20.44 Non-conforming Uses, Structures and Lot

Not applicable.

#### 20.48 Removal of Trees

Not applicable.

# 20.52 Flood Damage Prevention Regulations

Not applicable.

# 20.100.030 Use Permits.

Not applicable.

# 20.100.040 Variances.

Not applicable.

# 20.100.010 Common Permit Procedures.

Public notice of this application was mailed on September 30, 2011, in the form of mailed notice, to property owners and occupants within a 100-foot radius, and posted in three locations.

20.100.050 Design Review.

See Summary of Key Issues.

# ATTACHMENT 2 - FINDINGS

# Findings for Design Review approval (Per section 20.100.050.E of the AMC)

Required Finding		Explanation
1.	The project conforms to the General Plan, any applicable specific plan, applicable design guidelines adopted by the City of Albany, and all applicable provisions of this Chapter.	The General Plan designates this area for residential development. Additionally, the project meets City zoning standards for location, intensity and type of development.
2.	Approval of project design is consistent with the purpose and intent of this section, which states "designs of projectswill result in improvements that are visually and functionally appropriate to their site conditions and harmonious with their surroundings, including natural landforms and vegetation. Additional purposes of design review include (but are not limited to): that retention and maintenance of existing buildings and landscape features are considered; and that site access and vehicular parking are sufficient."	The proposal is in scale and harmony with existing development in the vicinity of the site. The architectural style, design and building materials are consistent with the City's Residential Design Guidelines. The project will not require significant grading or excavation. The project will not create a visual detriment at the site or the neighborhood.  The proposed addition is attractive in appearance, and is in scale with the surrounding neighbors. The design is complementary with the existing home.
3.	Approval of the project is in the interest of public health, safety and general welfare.	The proposed project will not be detrimental to the health, safety, convenience and welfare of those in the area and would not adversely impact property, improvements or potential future development in the area.
4.	The project is in substantial compliance with applicable general and specific Standards for Review stated in Subsection 20.100.050.D.	The project as designed is in substantial compliance with the standards as stated, including harmonious materials, and well proportioned massing.

# ATTACHMENT 3 COMMUNITY DEVELOPMENT DEPARTMENT CONDITIONS OF APPROVAL

#### **GENERAL PROJECT CONDITIONS**

- Gen-1 **Project Approval**. This Design Review approval is for 918 Cerrito St., as substantially shown and described on the project plans, except as may be modified by conditions herein. Plans prepared by Howard McNenny, Project Architect, date received September 1, 2011, as presented to the Planning and Zoning Commission on October 11, 2011. For any condition herein that requires preparation of a Final Plan where the project developer has submitted a conceptual plan, the project developer shall submit final plan(s) in substantial conformance with the conceptual plan, but incorporate the modifications required by the conditions herein for approval by the City.
- GEN-2 **Project Approval Expiration**. This Design Review approval expire on October 25, 2012 (one year from the date on which this approval becomes effective) or at an alternate time specified as a condition of approval, unless a building permit has been issued and construction diligently pursued. The approval may be renewed by the Community Development Director for a period up to an additional two (2) years, provided that, at least ten (10) days before expiration of one (1) year from the date when the approval becomes effective, an application for renewal of the approval is filed with the Community Development Department. The Community Development Director may grant a renewal of an approval where there is no change in the original application, or there is no request to change any condition of approval.
- Gen-3 FEES. The applicant shall pay any and all City and other related fees applicable to the property, as may be modified by conditions herein. Fees shall be based on the current fee structure in effect at the time the relevant permits are secured, and shall be paid before issuance of said permit or before any City Council final action approval. Notice shall be taken specifically of Plan Check, Engineering, Fire and Inspection Fees. The project developer shall also reimburse the City for direct costs of planning; building and engineering plan check and inspection, as mutually agreed between the City and developer.
- GEN-4 **Appeals**. The Albany Municipal Code provides that any action of the Planning staff may be appealed to the Planning and Zoning Commission, and any action of the Planning and Zoning Commission may be appealed to the City Council as per the procedures described in Section 20.100.080. The City Clerk will then schedule the matter for the next available City Council meeting.
- GEN-5 **Requirement for Building Permit**. Approval granted by the Planning and Zoning Commission does not constitute a building permit or authorization to begin any construction or demolish an existing structure. An appropriate permit issued by the Community Development Department must be obtained before constructing, enlarging, moving, converting, or demolishing any building or structure within the City.

- GEN-6 **Fire Department Approval**. As part of a building permit application, the applicant shall submit written documentation that all requirements of the Albany Fire Department have, or will be, met to the satisfaction of the AFD.
- GEN-7 **Engineering Approval**. As part of a building permit application, the applicant shall submit written documentation that all requirements of the Public Works Department have, or will be, met to the satisfaction of the City Engineer.
- GEN-8 **Construction Hours**. Construction activity shall be restricted to the hours of 8:00 a.m. to 6:00 p.m. Mondays through Saturdays, and 10:00 a.m. to 6:00 p.m., Sundays and legal holidays, unless otherwise approved in writing by the City Engineer for general construction activity. Failure to comply with construction hours may result in stop work orders or other administrative actions.
- GEN-9 Archeological Remains. In the event subsurface archeological remains are discovered during any construction or preconstruction activities on the site, all land alteration work within 100 feet of the find shall be halted, the Community Development Department notified, and a professional archeologist, certified by the Society of California Archeology and/or the Society of Professional Archeology, shall be notified. Site work in this area shall not occur until the archeologist has had an opportunity to evaluate the significance of the find and to outline appropriate mitigation measures, if deemed necessary. If prehistoric archeological deposits are discovered during development of the site, local Native American organizations shall be consulted and involved in making resource management decisions.
- Modifications to Approved Plans. The project shall be constructed as approved. Planning staff may approve minor modifications in the project design, but not the permitted land use (per MC 20.12). A change in an item requiring discretionary approval and any other changes deemed appropriate by the Planning staff shall require further Planning and Zoning Commission approval through the Design Review process.
- GEN-11 Hold Harmless Agreement. Pursuant to Government Code Section 66474.9, the applicant (including any agent thereof) shall defend, indemnify, and hold harmless, the City of Albany and its agents, officers and employees, from any claim, action, or proceeding against the City or its agents, officers or employees to attack, set aside, void, or annul the City's approval concerning this application, which action is brought within the time period provide for in Section 66499.37. The City will promptly notify the applicant of any such claim action or proceeding and cooperate fully in the defense.
- GEN-12 **Public Improvements Standards**. Public improvements shall be designed and constructed in accordance with the City's Standard Specifications and Standard Details, unless specifically waived in writing by the City Engineer.

- GEN-13 **Title 24 Standards**. All construction shall be designed and built in accordance with California Title 24 handicap accessibility standards. Appropriate details and specifications shall be incorporated into the plans and submitted at time of building permit application.
- GEN-14 **Energy Conservation Standards**. All buildings shall be designed in accordance with the State of California energy conservation standards for non-residential buildings. The necessary plans and documentation shall be submitted at time of building permit application.

#### **ARCHITECTURE CONDITION**

- ARCH-1 **Material Samples**. Descriptions or samples of final exterior materials and the proposed color palette shall be submitted for review and approval by the Community Development Department as part of building permit application.
- ARCH-2 **Final Architectural Drawings**. The applicant shall submit final architectural elevations, details and revisions for the review and approval of the Community Development Department as part of building permit application.
- ARCH-3 **Window Recess**. All new windows shall be recessed two inches from face of building to provide adequate shade and shadow and to promote visual relief. Final window details shall be submitted for review and approval at the time of building permit application.
- ARCH-4 **Non-Reflective Glazing**. Any glazing material shall be non-reflective.

#### LIGHTING CONDITIONS

- Exterior Lighting. All exterior lighting shall be installed in such a manner that glare is directed away from surrounding properties and rights-of-way. If required, exterior light fixtures shall be equipped with "cut off" lenses to minimize light and glare spill over onto adjacent properties.
- LGHT-2 **Shielding of Lighting**. Prior to the certificate of occupancy, all accent lighting shall be directed downward and, if necessary, fixed with cut-off lenses to ensure that no glare spills onto neighboring properties.

#### **LANDSCAPING CONDITIONS**

LNDSC-1 **Street Tree Requirement**. The applicant shall apply for one street tree before the issuance of the building permit. The City's Environmental Resource Assistance will determine the type and location of the tree and may waive this requirement if site conditions will not reasonably support establishment of a new tree.

#### PUBLIC WORKS DEPARTMENT CONDITIONS

#### **GENERAL ENGINEERING CONDITIONS**

- ENGR-1 **Title Report**. n/a.
- ENGR-2 **Geo-Technical Report**. The applicant shall submit, as part of a building permit application, a geotechnical investigation report prepared by a California certified engineering geologist and geotechnical engineer, if determined necessary by the City Engineer. The investigation shall specifically address any hazards of surface fault rupture in accordance with the Alquist-Priolo Special Study Zones Act. Any mitigation measures or conditions requiring further review noted during the Planning process shall be fully addressed prior to plan check.
- ENGR-3 **Backflow Device**. Any required water service for fire protection purposes shall be equipped with a City approved backflow device. Services for irrigation purposes also require a separate City approved backflow prevention device.

#### **GRADING CONDITIONS**

- GRAD-1 **Grading Permit**. Any grading required in association with the project shall require a grading permit from the Community Development Department. To obtain this permit, the applicant shall submit a grading plan, indicating the extent and volumes of earth proposed to be moved. A grading permit is subject to 2001 California Building, Appendix 33.
- GRAD-2 **Demolition Permit**. Site demolition shall not occur until construction permits are issued for the development project. All demolition shall be in accordance with permits issued by the City and Bay Area Air Quality Management District (BAAQMD).
- Water on Site. The site shall be graded so as to prevent rainfall runoff originating from improved areas on the project site from crossing onto adjoining private property. Building floor elevations shall be above the FEMA-mapped 100-year flood plain as established by a licensed civil engineer. Provide the elevation and compaction certificates during and upon the completion of grading required by the Uniform Building Code and in conformance with the recommendations of the geotechnical engineer's report. Shore and dewater all excavations in accordance with the requirements of the geotechnical engineer's report.
- GRAD-4 Flooding Damages. The project developer shall execute an assumption of risk, indemnification and hold harmless agreement as required by the City. The agreement, in substance, shall state that the project developer, and any successor in interest, shall assume all risk for damages to the project and to project improvements, flooding caused by surface water intrusion, stormwater runoff, or water under the ground surface pressing on or flowing or seeping through foundations, walls, floors, or paved surfaces, basements, whether paved or not, or windows, doors or other openings, and shall indemnify and hold the City

harmless from any claims of such damages, including third-party claims, of such damage or of such damages or of damages arising from rainfall runoff which is not prevented from leaving the project site in violation of Condition GRAD-3.

- GRAD-5 **Dust Control Program**. A dust control program shall be prepared by the project developer and approved by the Community Development Department and City Engineer before issuance of a grading permit. The dust control plan shall address such items as covering stockpiled material, frequent watering of graded areas, revegetating graded areas, speed limits for grading equipment and similar items.
- Stormwater Pollution Prevention Plan. The project developer shall submit a Stormwater Pollution Prevention Plan (SWPPP) for review by the City before the issuance of a building or grading and/or building permit. The SWPPP shall be consistent with standards adopted by the Regional Water Quality Control Board and the City of Albany Clean Water Program and implemented by the project general contractor, all subcontractors and suppliers of material and equipment. Construction site cleanup and control of construction shall also be addressed in the SWPPP. The project developer shall be responsible for SWPPP compliance. A copy of the SWPPP shall be kept at the construction site at all times.

#### INFRASTRUCTURE CONDITIONS

- INFR-1 **Sewer System Requirements**. The sewer system for the subject building shall comply with Chapter 15 of the Albany Municipal Code and to the satisfaction of the City Engineer before Final Inspection approval of the construction permit.
- INFR-2 **Two-Way Cleanout.** Installation of a two-way curbside cleanout shall be required per Chapter 15 of the Albany City Code. This applies to all properties, including properties with a valid upper sewer lateral certificate of compliance. All 2-way curbside clean outs shall be fitted with a loose cap in accordance with the City's standard detail SS6.
- INFR-3 **Property Run-off Requirements**. All runoff from impervious surfaces shall be intercepted at the project boundary and shall be collected and conducted via an approved drainage system through the project site to an approved storm drain facility, as determined by the City Engineer. Development that contributes additional water to the existing drainage system shall be required to complete a hydraulic study and make improvements to the system as required to accommodate the expected ultimate peak water flow and to stabilize erosive banks that could be impacted by additional storm water flow.
- Roof Drainage. Roof drainage from the structure shall be collected via a closed pipe and conveyed to an approved storm drain system off the street curb. No concentrated drainage of surface flow across sidewalks shall be permitted. Alternative natural treatment measures are subject review and approval by the City Engineer.

- INFR-5 **Hydraulic Calculations**. The applicant shall submit hydraulic calculations, prepared by a California licensed civil engineer, necessary to determine if the existing water and sewer mains that serve this lot have available capacity for the addition of the proposed development. If capacity is not available, sewer and water mains of adequate size shall be designed and secured prior to issuance of building permits and constructed in a manner acceptable to the City Engineer prior to occupancy release, unless determined otherwise by the City Engineer.
- INFR-6 **Completion of Off-Site Improvements**. Off-site improvements, as required by the City Engineer, shall be complete before issuance of a Certificate of Occupancy unless alternatives are approved in writing by the Albany City Engineer.

#### **PUBLIC IMPROVEMENTS CONDITIONS**

- PUBIM-1 **Encroachment Permit**. The applicant shall obtain an encroachment permit from the Engineering Division before commencing any construction activities within any public right-of-way or easement.
- PUBIM-2 **Debris Removal.** All mud, dirt or construction debris carried off the construction site onto adjacent streets shall be removed each day. No materials shall be discharged onto a sidewalk, street, gutter, storm drain or creek.
- PUBIM-3 **Damage to Street Improvements**. Any damage to street improvements now existing or done during construction on or adjacent to the subject property, shall be repaired to the satisfaction of the City Engineer at the full expense of the applicant. This shall include sidewalk repair, slurry seal, street reconstruction or others, as may be required by the City Engineer.
- PUBIM-4 **Right-of-Way Construction Standards**. All improvements within the public right-of-way, including curb, gutter, sidewalks, driveways, paving and utilities, shall be reconstructed in accordance with approved standards and/or plans and shall comply with the standard plans and specification of the Community Development Department and Chapter 14 of the City Code.

#### FIRE DEPARTMENT CONDITIONS

- FIRE-1 **Construction of 1,500 Square Feet or Greater**. 1500 sq. ft. or more or any addition, remodel, rehabilitation, etc. is 50% of the existing sq. ft.:
  - a) This dwelling will be required install an Automatic Fire Extinguishing System throughout the entire dwelling. Ordinance No. 94-010, Albany Municipal Code, Chapter 11, Section 11-2.3a(3)(a).
  - b) Plans, information sheets on all sprinkler components and hydraulic calculations are required.
  - c) A 110-volt interconnected smoke alarm system with a 10-year lithium battery back-up is acceptable with a fire suppression system.

- FIRE-2 **Fire Rated Construction**. Any portion of a building five (5) feet or less from the property line shall comply with fire-rating requirements of the CBC.
- Gallons-per-Minute Requirement. The water system for fire protection shall comply with City of Albany Fire Department standards. Fire flow test data and water system plans must be provided at time of building plan check. The plans must include all equipment, components and layout of the system. Private fire protection water systems shall be supplied through an approved backflow device per City Engineering Division standards.
- Distance From Fire Hydrant. Before building permit issuance the distance from existing fire hydrants to the building shall be verified and if necessary, a new hydrant shall be shown on the plans and installed prior to combustible construction.

#### STRUCTURAL CONTROL MEASURES

- STRUC-1 **Illegal Dumping to Storm Drain Inlets and Waterways**. On-site storm drain inlets shall be clearly marked with the words "No Dumping! Flows to Bay," or equivalent, using methods approved by the City of Albany.
- Pesticide/Fertilizer Application Landscaping shall be designed to minimize irrigation and runoff, promote surface infiltration where appropriate, and minimize the use of fertilizers and pesticides that can contribute to stormwater pollution. If a landscaping plan is required as part of a development project application, the plan shall meet the following conditions related to reduction of pesticide use on the project site:
  - a) Where feasible, landscaping shall be designed and operated to treat stormwater runoff by incorporating elements that collect, detain, and infiltrate runoff. In areas that provide detention of water, plants that are tolerant of saturated soil conditions and prolonged exposure to water shall be specified.
  - b) Plant materials selected shall be appropriate to site specific characteristics such as soil type, topography, climate, amount and timing of sunlight, prevailing winds, rainfall, air movement, patterns of land use, ecological consistency and plant interactions to ensure successful establishment.
  - c) Existing native trees, shrubs, and ground cover shall be retained and incorporated into the landscape plan to the maximum extent practicable.
  - d) Proper maintenance of landscaping, with minimal pesticide use, shall be the responsibility of the property owner.

#### **OPERATIONAL BEST MANAGEMENT PRACTICES (BMPS)**

BMP-GEN1 **Stormwater Pollution Prevention Control Measures**. The project plans shall include stormwater pollution prevention and control measures for the operation and maintenance of the project during and after construction for the review and approval of the City or County Engineer. The project plan shall identify Best Management Practices (BMPs) appropriate to the uses conducted on-site in order

to limit to the maximum extent practicable the entry of pollutants into stormwater runoff.

- BMP-GEN2 **Erosion Control Measures**. The project plan shall also include erosion control measures to prevent soil, dirt and debris from entering the storm drain system, in accordance with the practices outlined in the ABAG *Erosion and Sediment Control Handbook*, California Storm Water Best Management Practice Handbooks, and Regional Water Quality Control Board's *Erosion and Sediment Control Field Manual*
- Responsibility of Contractors. The applicant is responsible for ensuring that all contractors and subcontractors are aware of and implement all stormwater quality control measures. Failure to comply with the approved construction BMPs shall result in the issuance of correction notices, citations and/or a project stop order.
- Paved Sidewalks and Parking Lots. Sidewalks and parking lots shall be swept regularly to prevent the accumulation of litter and debris. Debris resulting from pressure washing shall be trapped and collected to prevent entry into the storm drain system. Washwater containing any soap, cleaning agent or degreaser shall be collected and discharged to the sanitary sewer and shall not be discharged to a storm drain. The applicant shall contact the City Engineer for specific connection and discharge requirements.
- BMP-2A **Private Streets, Utilities and Common Areas.** The owner of private streets and storm drains shall prepare and implement a plan for street sweeping of paved private roads and cleaning of all storm drain inlets.

#### GENERAL CONSTRUCTION BEST MANAGEMENT PRACTICES (BMPs)

- BMP-CNST1 **Construction Access Routes**. Construction access routes shall be limited to those approved by the City Engineer and shall be shown on the approval grading plan.
- BMP-CNST2 **Collection of Construction Debris**. Gather all construction debris on a regular basis and place them in a dumpster or other container that is emptied or removed on a weekly basis. When appropriate, use tarps on the ground to collect fallen debris or splatters that could contribute to stormwater pollution.
- BMP-CNST3 **Removal of Waste**. Remove all dirt, gravel, rubbish, refuse and green waste from the sidewalk, street pavement, and storm drain system adjoining the project site. During wet weather, avoid driving vehicles off paved areas and other outdoor work.
- BMP-CNST4 **Sweeping of Public Right-of-Way**. Broom sweep the sidewalk and public street pavement adjoining the project site on a daily basis. Caked on mud or dirt shall be scraped from these areas before sweeping.

BMP-CNST5 **Filter Materials at Storm Drain Inlet**. Install filter materials (such as sandbags, filter fabric, etc.) at the storm drain inlet nearest the downstream side of the project site prior to:

- a) start of the rainy season (October 1);
- b) site dewatering activities;
- c) street washing activities;
- d) saw cutting asphalt or concrete; and
- e) order to retain any debris or dirt flowing into the City storm drain system. Filter materials shall be maintained and/or replaced as necessary to ensure effectiveness and prevent street flooding. Dispose of filter particles in the trash.

BMP-CNST6 **Containment of Materials**. Create a contained and covered area on the site for the storage of bags of cement, paints, flammables, oils, fertilizers, pesticides, or any other materials used on the project site that have the potential for being discharged to the storm drain system by wind or in the event of a material spill.

BMP-CNST7 **Cleaning of Equipment**. Never clean machinery, tools, brushes, etc. or rinse containers into a street, gutter, storm drain or stream. See the *Building Maintenance/ Remodeling* flyer for more information.

BMP-CNST8 **Minimize Removal of Natural Vegetation**. Minimize removal of natural vegetation or ground cover from the site in order to minimize the potential for erosion and sedimentation problems. Replant the area as soon as possible. All cut and fill slopes shall be stabilized as soon as possible after grading is completed. No site grading shall occur between October 1 and April 15 unless approved erosion and sedimentation control measures are in place.

#### **SPECIAL CONDITIONS**

SPECIAL 1 none.

#### Appeals:

The Albany Municipal Code provides that any action of the Planning and Zoning Commission may be appealed to the City Council if such appeal is filed within 14 calendar days of the date of action. Appeals may be filed in the Community Development Department by completing the required form and paying the required fee. The City Clerk will then schedule the matter for the next available City Council meeting.